



LINGJACK
林傑

PORTABLE FIRE EXTINGUISHER

1KG ABC STORED PRESSURE FIRE EXTINGUISHER

MODEL : C-1ASE

Specification :

- Capacity : 1 kg
- Extinguishing Medium : 40% ABC Dry Chemical Powder
- Propellant Type : Nitrogen
- Fire Rating : 5A,55B,C
- Class of Fire : A,B,C
- Discharge Time : 9.53 sec
- Discharge Range : 3 m
- Working Pressure : 14 bar
- Working Temperature : -20Deg C to +60 Deg C
- Finishing : RAL 3001
- Size : Dia. 85 x 320(H) mm
- Gross Weight (Approx.) : 2.0 kg



Features :

- Outdoor UV Resistance Polyester Powder Coated
- Durable Plastic Discharge Nozzle
- Suitable to Use on Live Electrical Equipment Up to 1000V
- Effective Suppression of Class A,B & C Fires


Standards : Manufactured in accordance with EN 3-7 : 2004 +A1:2007

Approvals : LPCB (UK), Wheel Mark (MED), CE Mark (PED)

Origin : Made in Singapore



EN3-7:2004 + A1:2007
Cert No. 501a



0832



0832

GOOD QUALITY GREAT SERVICES

www.lingjack.com