



# LINGJACK

## 林傑

## PORTABLE FIRE EXTINGUISHER

### 12KG ABC CARTRIDGE OPERATED FIRE EXTINGUISHER

MODEL : C-12ACE

#### Specification :

- Capacity : 12 kg
- Extinguishing Medium : 40% ABC Dry Chemical Powder
- Propellant Type : 225 gram CO<sub>2</sub>
- Fire Rating : 55A,233B,C
- Class of Fire : A,B,C
- Discharge Time : 25.8 sec
- Discharge Range : 10 m
- Working Pressure : 14 bar
- Working Temperature : -20Deg C to +60 Deg C
- Finishing : RAL 3001
- Hose Length : 620 mm
- Size : Dia. 181 x 654(H) mm
- Gross Weight (Approx.) : 18.0 kg



#### Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Suitable to Use on Live Electrical Equipment up to 1000V
- Effective Suppression of Class A,B & C Fires


**Standards :** Manufactured in accordance with EN 3-7:2004+A1:2007

**Approvals :** LPCB ( UK ), Wheel Mark ( MED ), CE Mark ( PED )

**Origin :** Made in Singapore



EN3-7:2004 + A1:2007  
Cert No. 501a



0832



0832

**GOOD QUALITY GREAT SERVICES**

[www.lingjack.com](http://www.lingjack.com)