



# LINGJACK

## 林傑

### 2KG ABC STORED PRESSURE FIRE EXTINGUISHER

**MODEL : C-2ASE**

**Specification :**

- Capacity : 2 kg
- Extinguishing Medium : 40% ABC Dry Chemical Powder
- Propellant Type : Nitrogen
- Discharge Time : 9.66 sec
- Discharge Range : 3 m
- Working Pressure : 14 bar
- Working Temperature : -20Deg C to +60 Deg C
- Size : Dia. 98 x 455(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 3.7 kg



**Features :**

- Outdoor UV Resistance Polyester Powder Coated
- Durable Plastic Discharge Nozzle
- Effective Suppression of Class A,B Fires
- Effective Suppression of Class C Fires  
(Only Applicable To LPCB Approval Model)
- Suitable to Use on Live Electrical Equipment Up to 1000V  
(Only Applicable To LPCB Approval Model)

**Standards :** Manufactured In Accordance With EN 3-7

**Approvals :** LPCB (UK), SETSCO (SG), BUREAU VERITAS (BV)


**Origin :** Made in Singapore

Ordering Matrix :

Com No.	Fire Rating	For Class Of Fire	Standard	Approval
20801018	13A, 55B	A, B, C	BS EN 3-7:2004+A1:2007	LPCB
20801000	13A, 55B	A, B	SS EN 3-7 : 2012	SETSCO
2080101800001	13A, 55B	A, B, C	BS EN 3-7:2004+A1:2007	BV (MED)



EN3-7:2004 + A1:2007  
Cert No. 501a



2690

**GOOD QUALITY GREAT SERVICES**

[www.lingjack.com](http://www.lingjack.com)